

ciency of these organic PV cells, the researchers found “that materials choice is an important route to cell optimization.” Hence, not only has efficiency been improved, but also the understanding of these devices.

PAMELA JOHNSON

The Femtosecond Transient Absorption Signal of UV-Grade Fused Silica Contains Third- and Fifth-Order Nonlinearities

Femtosecond transient absorption pump-probe spectroscopy and numerical simulations show interference between the third- and fifth-order nonlinear susceptibilities ($\chi^{(3)}$, $\chi^{(5)}$) of ultraviolet (UV)-grade fused silica. Katrin Ekvall of the Royal Institute of Technology in Stockholm and Cecilia Lundevall and Peter van der Meulen of Stockholm University have obtained values for the second-order nonlinear refractive index and the three-photon absorption (3 PA) coefficient from $\chi^{(5)}$.

As reported in the June 15 issue of *Optics Letters*, a compact Ti:sapphire amplified fs laser system produced ~850 μJ , 160 fs pulses centered at 775 nm. A 0.2-mm-thick Type I β -barium borate second-harmonic generation crystal frequency doubled the fundamental pulse to produce a pump pulse with $\lambda = 387.5$ nm.

White light continuum probe and reference pulses were obtained by focusing a small fraction of the fundamental pulse in a thin rotating fused-silica plate. Both the third- and fifth-order material responses produce large signals in the detected region.

The intensity of the pump pulse was varied from 90 to 160, 210, and 270 GW/cm^2 by rotating a zero-order half-wave plate in front of the β -barium borate crystal.

At the lowest intensity, the transient absorption signal was W-shaped. At higher intensities the curve developed an extra dip and the signal increased. The researchers describe the signal as a superposition of three contributions: the real part of $\chi^{(3)}$, dominant at the lowest intensity; a similarly shaped effect with opposite sign from the real part of $\chi^{(5)}$, which produces the dip at higher intensities; and the imaginary part of $\chi^{(5)}$, corresponding to 3 PA.

The researchers numerically solved the probe propagation equation in the presence of third- and fifth-order nonlinearities, obtaining the probe amplitude after propagation through the sample. They calculated the pump-probe signal as a function of probe wavelength and the delay time between the pump and the probe.

A comparison with the experiment gave the real and imaginary parts of $\chi^{(5)}$. The real part is $-5.1(\pm 0.7) \times 10^{-41} \text{ m}^4/\text{V}^4$, which gives for the second order nonlinear refractive index $-3.3(\pm 0.4) \times 10^{-41} \text{ m}^4/\text{V}^4$. The error is due to the uncertainty in pump intensity. The imaginary part of $\chi^{(5)}$ is $2.1(\pm 0.3) \times 10^{-41} \text{ m}^4/\text{V}^4$, which gives for the 3 PA coefficient $5.2(\pm 0.7) \times 10^{-29} \text{ m}^3/\text{W}^2$. The simulations did not accurately reproduce the measurements at the highest optical pump intensity, indicating the possibility that even higher order processes may play a role in the nonlinear optical response of this glass.

ELIZABETH A. SHACK

Photopatterned Films of Discotic Liquid Crystals Demonstrate Polarized Photoluminescence

The ability to control the orientation of liquid crystals (LCs) is needed to optimize their properties for use in display devices. As reported in a communication for the May issue of *Chemistry of Materials*, in a collaborative effort led by Kunihiro Ichimura of the Tokyo Institute of Technology, researchers used a micropatterned film of discotic liquid crystals (DLCs) to demonstrate the first observation of their polarized photoluminescence (PL).

To date, research in the field of DLCs trails that of calamitic liquid crystals (CLCs) due to the relative difficulties of assembling well-defined DLCs. This is due to the high viscosity of DLCs, and their high mesophase temperatures. To overcome these obstacles, the researchers first assembled a thin film that aided orientation, followed by a heating method which aided in the ordering of the liquid crystals (DLCs).

The researchers first assembled a thin film (25 nm) by spin-coating a 1.0 wt% solution of poly[4-(4-cyanophenylazo)phenoxy] methacrylate] (A) on a silica plate. This thin film was then subjected to nonpolarized 436-nm light of 3.0 J cm^{-2} fluence with an angle of 45°, which induced photodichroism. Annealing A at 240°C for 30 minutes then enhanced the anisotropy of the film. Micropatterning of the DLCs was achieved by photoirradiation through a photomask upon A before the addition of DLCs.

This prepared film aided in the organized assembling of the DLCs. Next, two DLCs were spin-cast onto the thin film A: both pentakis[(4-alkylphenyl)ethyl]benzene derivatives, labeled as DLC-1 and DLC-2. The films were heated and supercooled, which preserved and aided in the orientation of both DLC-1 and DLC-2. A study of the three-dimensional orientation revealed that both DLCs have

homeotropic alignments, with angles of 70° from the surface A. This was demonstrated by monitoring the azimuthal retardation as a function of the angle of incidence of the probe light, which yielded asymmetrical plots.

To further probe the alignment of the DLC films, PL measurements illustrated the outermost DLCs' alignment at a microscopic level. This alignment was found to be an opposite tilt to the actinic light propagation. When DLC-1/A was irradiated under nonpolarized 340-nm excitation at 20° to the surface normal, distinct s-polarized, and p-polarized PL absorbances were demonstrated. Both intensity peaks were at ~460 nm, despite the nonpolarized excitation. The s-polarized/p-polarized intensity ratio was ~3. These results show that the 3D ordering of the preliminary A film was transferred to the DLCs' surface.

Also included in this report is an image of the micropatterned DLC films under PL, demonstrating both s-polarized and p-polarized PL, while visually demonstrating the propensity for applications in display devices. These DLCs were shown to be stable in ambient conditions for greater than six months. This communication demonstrates an investigation into the orientation of DLCs via PL, and a possible fabrication technique that results in better control of such orientation. Better orientational control of DLCs will enhance the performance of DLC-based devices such as thin film displays.

MATHEW M. MAYE

SrTiO₃ Single Crystals Achieve 8% Plastic Strain When Tested in Compression at Room Temperature

Ceramic oxides tend to fail mainly by brittle fracture at ambient or low-temperatures, due to the ionic and covalent nature of the atomic bonding. However, a group of researchers from the Max Planck Institute in Stuttgart has obtained plastic deformation in compression from SrTiO₃, a ceramic oxide with a perovskite structure. The researchers observed a ductile–brittle–ductile transition when testing in a range of temperatures from 78 K to 1800 K, as reported in the May issue of the *Journal of the American Ceramic Society*. The samples were ductile in the temperature ranges from 78 K to 1050 K and between 1500 and 1800 K, and brittle between 1050 K and 1500 K.

In order to gather basic information about the nature of the deformation mechanism on this material, the researchers tested single crystals of SrTiO₃ oriented with the <001> axis parallel to the compression axis. Tests were conducted in air